


**SILICON EPITAXIAL SWITCHING DIODE**

**1N914WS**



**SOD-323  
PLASTIC PCAKAGE**

**Marking**

1N914WS=WQ with cathode band

Small Signal Diode

**ABSOLUTE MAXIMUM RATINGS ( T<sub>a</sub>=25°C)**

DESCRIPTION	SYMBOL	VALUE	UNIT
Repetitive Peak Reverse Voltage	V <sub>RRM</sub>	100	V
Average Rectified Forward Current	I <sub>F (AV)</sub>	200	mA
Non Repetitive Peak Forward Surge Current	I <sub>FSM</sub>		
Pulse width=1s		0.5	A
Pulse width=1ms		1.0	A
Power Dissipation	P <sub>tot</sub>	200	mW
Junction Temperature	T <sub>j</sub>	150	°C
Storage Temperature Range	T <sub>stg</sub>	- 55 to +150	°C

**THERMAL RESISTANCE**

Junction to Ambient in free air	R <sub>th (j-a)</sub>	312	°C/W
---------------------------------	-----------------------	-----	------

**ELECTRICAL CHARACTERISTICS ( T<sub>a</sub>=25°C unless specified otherwise)**


DESCRIPTION	SYMBOL	TEST CONDITION	MIN	MAX	UNIT
Breakdown Voltage	V <sub>R</sub>	I <sub>R</sub> =5μA	75		V
		I <sub>R</sub> =100μA	100		V
Forward Voltage	V <sub>F</sub>	I <sub>F</sub> =10mA		1.0	V
Reverse Current	I <sub>R</sub>	V <sub>R</sub> =20V		25	nA
		V <sub>R</sub> =20V, T <sub>j</sub> =150°C		50	μA
		V <sub>R</sub> =75V		5.0	μA
<b>DYNAMIC CHARACTERISTICS</b>					
Capacitance	C <sub>tot</sub>	V <sub>R</sub> =0V, f=1MHz		4.0	pF
Reverse Recovery Time	t <sub>rr</sub>	I <sub>F</sub> = I <sub>R</sub> =30mA, R <sub>L</sub> =100Ω, I <sub>RR</sub> =3.0mA		50	ns

1N914WS Rev170507E

**1N914WS**

**SOD-323  
PLASTIC PCAKAGE**

PACKAGE SOD-323 FL



All dimensions are in mm

CATHODE IS MARKED BY BAND

**1N914WS Rev170507E**

**Component Disposal Instructions**

1. CDIL Semiconductor Devices are RoHS compliant, customers are requested to please dispose as per prevailing Environmental Legislation of their Country.
2. In Europe, please dispose as per EU Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE).

**Disclaimer**

The product information and the selection guides facilitate selection of the CDIL's Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of  
Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.  
Telephone + 91-11-2579 6150, 4141 1112 Fax + 91-11-2579 5290, 4141 1119  
email@cdil.com www.cdilsemi.com