



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001/ISO 45001 Certified Company



HIGH SPEED SILICON SWITCHING DIODE

1N4148

1N4448



DO-35



**DO-35 Leaded
Glass Axial Package
RoHS compliant**

FEATURES:

1. Polarity : Colour band denotes cathode end
2. This product is available in AEC-Q101 Compliant and PPAP Capable also.

Note: For AEC-Q101 compliant products , please suffix - AQ in the part number while ordering

APPLICATION:

General purpose, Industrial, Military and Space applications. Hermetically sealed glass with a stud on either side of the glass passivated chip provides excellent stability. Extremely low leakage and very high reliability.

ABSOLUTE MAXIMUM RATINGS (Ta = 25 °C Unless otherwise specified)

PARAMETER	SYMBOL	VALUE	UNIT
Maximum Repetitive Reverse Voltage	V_{RRM}	100	V
Continuous Reverse Voltage	V_R	75	V
Average Rectified Forward Current	$I_{(AV)}$	200	mA
DC Forward Current	I_F	300	mA
Recurrent Peak Forward Current	I_P	400	mA
Non-Repetitive Peak Forward Surge Current	I_{FSM}	Pulse Width=1.0s	1.0
		Pulse Width=1.0µs	4.0
Power Dissipation	P_D	500	mW
Storage Temperature Range	T_{STG}	-65 to +200	°C
Operating Junction Temperature Range	T_J	-65 to +175	°C

THERMAL RESISTANCE

Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	300	°C/W
---	-----------------	-----	------

1N4148_4448
Rev05 07092023E



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001/ISO 45001 Certified Company



ELECTRICAL CHARACTERISTICS at (Ta = 25 °C Unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	VALUE			UNIT
				MIN	TYP	MAX	
Forward Voltage	1N4148	V _F	I _F =10mA	--	--	1.0	V
	1N4448		I _F =5mA	0.62	--	0.72	V
			I _F =100mA	--	--	1.0	V
Reverse Leakage		I _R	V _R =20V	--	--	25	nA
			V _R =20V; T _A = 150°C	--	--	50	µA
			V _R =75V	--	--	5.0	µA
Reverse Breakdown Voltage		V _{BR}	I _R =100µA	100	--	--	V
			I _R =5µA	75	--	--	V
Diode Capacitance	1N4148	C _T	V _R =0; f = 1.0MHz	--	--	4	pF
	1N4448			--	--	2	pF
Reverse Recovery Time		t _{rr}	I _F =10mA to I _R =60mA, R _L =100Ω measured at I _R =1mA	--	--	4	ns

Note:

1. These ratings are limiting values above which the serviceability of the diode may be impaired.
2. Non-recurrent square wave P_w = 8.3ms

1N4148_4448
Rev05 07092023E



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001/ISO 45001 Certified Company



TYPICAL CHARACTERISTICS CURVES

Fig 1: Forward Voltage vs. Junction Temperature




Fig 3: Reverse Current vs. Reverse Voltage






Fig 2: Forward Current vs. Forward Voltage



1N4148_4448
Rev05 07092023E

Package Details

DO-35 Leaded Glass Axial Package



DIM	MIN	MAX
A	25.4	38.1
B	3.05	5.08
C	0.46	0.55
D	1.53	2.28
L1	--	1.27



Unit :mm

Lead diameter not controlled in zone L1 to allow for flash, lead finish build-up and minor irregularities other than heat slugs.

Note : Cathode is marked by Black Band

DO-35 TAPING SPECIFICATION

1. T & A Indicate Axial Tape & AMMO Packing (52mm Tape Spacing)
2. 300mm (min) Leader Tape On Every spool.
3. No of empty Places Allowed 0.25% without Consecutive Empty Places
4. End of Leads shall Preferably not protrude beyond the Tapes.
5. Components Shall be held sufficiently in the tape or tapes so that they can not come free in normal handling



Recommended Reflow Solder Profiles

The recommended reflow solder profiles for Pb and Pb-free devices are shown below.

Figure 1 shows the recommended solder profile for devices that have Pb-free terminal plating, and where a Pb-free solder is used.

Figure 2 shows the recommended solder profile for devices with Pb-free terminal plating used with leaded solder, or for devices with leaded terminal plating used with a leaded solder.

Figure 1





Figure 2





Reflow profiles in tabular form

Profile Feature	Sn-Pb System	Pb-Free System
Average Ramp-Up Rate	~3°C/second	~3°C/second
Preheat		
– Temperature Range	150-170°C	150-200°C
– Time	60-180 seconds	60-180 seconds
Time maintained above:		
– Temperature	200°C	217°C
– Time	30-50 seconds	60-150 seconds
Peak Temperature	235°C	260°C max.
Time within +0 -5°C of actual Peak	10 seconds	40 seconds
Ramp-Down Rate	3°C/second max.	6°C/second max.

Recommended Wave Solder Profiles

The Recommended solder Profile For Devices with Pb-free terminal plating where a Pb-free solder is used

The Recommended solder Profile For Devices with Pb-free terminal plating used with leaded solder, or for devices with leaded terminal plating used with leaded solder



Wave Profiles in Tabular Form

Profile Feature	Sn-Pb System	Pb-free System
Average Ramp-Up Rate	~200°C/second	~200°C/second
Heating rate during preheat	Typical 1-2, Max 4°C/sec	Typical 1-2, Max 4°C/Sec
Final preheat Temperature	Within 125°C of Solder Temp	Within 125°C of Solder Temp
Peak Temperature	235°C	260°C max.
Time within +0 -5°C of actual Peak	10 seconds	10 seconds
Ramp-Down Rate	5°C/second max.	5°C/second max.



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001/ISO 45001 Certified Company



Recommended Product Storage Environment for Discrete Semiconductor Devices

This storage environment assumes that the Diodes and transistors are packed properly inside the original packing supplied by CDIL.

- Temperature 5 °C to 30 °C
- Humidity between 40 to 70 %RH
- Air should be clean.
- Avoid harmful gas or dust.
- Avoid outdoor exposure or storage in areas subject to rain or water spraying .
- Avoid storage in areas subject to corrosive gas or dust. Product shall not be stored in areas exposed to direct sunlight.
- Avoid rapid change of temperature.
- Avoid condensation.
- Mechanical stress such as vibration and impact shall be avoided.
- The product shall not be placed directly on the floor.
- The product shall be stored on a plane area. They should not be turned upside down. They should not be placed against the wall.

Shelf Life of CDIL Products

The shelf life of products is the period from product manufacture to shipment to customers. The product can be unconditionally shipped within this period. The period is defined as 2 years.

If products are stored longer than the shelf life of 2 years the products shall be subjected to quality check as per CDIL quality procedure.

The products are further warranted for another one year after the date of shipment subject to the above conditions in CDIL original packing.

Floor Life of CDIL Products and MSL Level

When the products are opened from the original packing, the floor life will start.

For this, the following JEDEC table may be referred:

JEDEC MSL Level		
Level	Time	Condition
1	Unlimited	≤30 °C / 85% RH
2	1 Year	≤30 °C / 60% RH
2a	4 Weeks	≤30 °C / 60% RH
3	168 Hours	≤30 °C / 60% RH
4	72 Hours	≤30 °C / 60% RH
5	48 Hours	≤30 °C / 60% RH
5a	24 Hours	≤30 °C / 60% RH
6	Time on Label(TOL)	≤30 °C / 60% RH

1N4148_4448
Rev05 07092023E



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001/ISO 45001 Certified Company



Customer Notes

Component Disposal Instructions

1. CDIL Semiconductor Devices are RoHS compliant, customers are requested to please dispose as per prevailing Environmental Legislation of their Country.
2. In Europe, please dispose as per EU Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE).

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered trademark of

Continental Device India Pvt. Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone +91-11-2579 6150, 4141 1112 Fax +91-11-2579 5290, 4141 1119

email@cdil.com www.cdil.com

CIN No. U32109DL1964PTC004291

1N4148_4448

Rev05 07092023E