

## Silicone Epitaxial Planar Switching Diode

**1N4449**

**DO-35**  
**Glass Axial Package**  
**RoHS compliant**



DO-35

**Application:** For General purpose use and in switching applications

**Absolute Maximum Ratings** ( $T_a=25^\circ\text{C}$ )

Parameters	Symbol	Value	Unit
Peak reverse Voltage	$V_{RM}$	100	V
Reverse Voltage	$V_R$	50	V
Average Rectified Forward Current	$I_{F(AV)}$	200	mA
Surge Forward Current	$I_{FSM}$	400	mA
Power Dissipation	$P_{tot(1)}$	500	mW
Junction Temperature	$T_j$	200	$^\circ\text{C}$
Storage Temperature Range	$T_{stg}$	-65 to 200	$^\circ\text{C}$

**Notes:**

1.Valid provided that leads at as distance of 8mm from case are kept at ambient temperature

### Electrical Characteristics

( $T_a=25^\circ\text{C}$  unless otherwise specified)

Parameters	Symbol	Test Conditions	Value		Unit
			Min.	Max.	
Forward Voltage	$V_F$	At $I_F=30\text{mA}$	--	1.0	V
Reverse Leakage Current	$I_R$	At $V_R=20\text{V}$	--	25	nA
Reverse Breakdown Voltage	$V_{(BR)V}$	At $I_R=150\mu\text{A}$	--	100	V
Reverse Recovery Time	$t_{rr}$	at $I_{rF}=10\text{mA}$ to $I_R=1\text{mA}$ , $I_{tr}=0.1 \times I_R$ , $V_R=6\text{V}$ , $R_L=100\Omega$	--	4	nS






Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



## TYICAL CHARACTERISTIVS CURVES



1N4449  
Rev0\_05052020EGL




Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



### Package details



Glass Case DO-35  
Dimensions in mm

1N4449  
Rev0\_05052020EGL



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



## **Recommended Product Storage Environment for Discrete Semiconductor Devices**

This storage environment assumes that the Diodes and transistors are packed properly inside the original packing supplied by CDIL.

- Temperature 5 °C to 30 °C
- Humidity between 40 to 70 %RH
- Air should be clean.
- Avoid harmful gas or dust.
- Avoid outdoor exposure or storage in areas subject to rain or water spraying .
- Avoid storage in areas subject to corrosive gas or dust. Product shall not be stored in areas exposed to direct sunlight.
- Avoid rapid change of temperature.
- Avoid condensation.
- Mechanical stress such as vibration and impact shall be avoided.
- The product shall not be placed directly on the floor.
- The product shall be stored on a plane area. They should not be turned upside down. They should not be placed against the wall.

### **Shelf Life of CDIL Products**

The shelf life of products is the period from product manufacture to shipment to customers. The product can be unconditionally shipped within this period. The period is defined as 2 years

If products are stored longer than the shelf life of 2 years the products shall be subjected to quality check as per CDIL quality procedure.

The products are further warranted for another one year after the date of shipment subject to the above conditions in CDIL original packing.

### **Floor Life of CDIL Products and MSL Level**

When the products are opened from the original packing, the floor life will start.

For this, the following JEDEC table may be referred:

<b>JEDEC MSL Level</b>		
<b>Level</b>	<b>Time</b>	<b>Condition</b>
1	Unlimited	≤30 °C / 85% RH
2	1 Year	≤30 °C / 60% RH
2a	4 Weeks	≤30 °C / 60% RH
3	168 Hours	≤30 °C / 60% RH
4	72 Hours	≤30 °C / 60% RH
5	48 Hours	≤30 °C / 60% RH
5a	24 Hours	≤30 °C / 60% RH
6	Time on Label(TOL)	≤30 °C / 60% RH

1N4449  
Rev0\_05052020EGL



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



## Customer Notes

### Component Disposal Instructions

1. CDIL Semiconductor Devices are RoHS compliant, customers are requested to please dispose as per prevailing Environmental Legislation of their Country.
2. In Europe, please dispose as per EU Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE).

### Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



**Continental Device India Pvt. Limited**

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone +91-11-2579 6150, 4141 1112 Fax +91-11-2579 5290, 4141 1119

email@cdil.com www.cdil.com

CIN No. U32109DL1964PTC004291

1N4449

Rev0\_05052020EGL