

NPN HIGH VOLTAGE SILICON TRANSISTORS

2N3439
2N3440



TO-39

TO-39
Metal Can Package
RoHS compliant

FEATURE:

1. This product is available in AEC-Q101 Compliant and PPAP Capable also.

Note: For AEC-Q101 compliant products, please use suffix -AQ in the part number while ordering.

APPLICATIONS: High Voltage Silicon Planar Transistors used in High Voltage & High Power Amplifier

ABSOLUTE MAXIMUM RATINGS (Ta = 25 °C Unless otherwise specified)

PARAMETER	SYMBOL	2N3439	2N3440	UNIT
Collector -Emitter Voltage	V_{CEO}	350	250	V
Collector -Base Voltage	V_{CBO}	450	300	V
Emitter -Base Voltage	V_{EBO}	7.0		V
Collector Current Continuous	I_C	1.0		A
Base Current	I_B	0.5		A
Power Dissipation@ Ta=25°C	P_D	1.0		W
Derate Above 25°C		5.7		mW/°C
Power Dissipation@ Tc=25°C	P_D	5.0		W
Derate Above 25°C		28.6		mW/°C
Operating And Storage Junction Temperature Range	T_j, T_{stg}	-65 to +200		°C

THERMAL RESISTANCE

Junction to Case	$R_{th(j-c)}$	35	°C/W
Junction to Ambient in free air	$R_{th(j-a)}$	175	

ELECTRICAL CHARACTERISTICS at (Ta = 25 °C Unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS		2N3439	2N3440	UNIT
Collector -Emitter Voltage	$V_{CE(sus)}^1$	$I_C=50mA, I_B=0$	Max	350	250	V
Collector-Cut off Current	I_{CBO}	$V_{CB}=360V, I_E=0$	Min	20	--	μA
		$V_{CB}=250V, I_E=0$	Min	--	20	μA
	I_{CEO}	$V_{CE}=300V, I_B=0$	Min	20	--	μA
		$V_{CE}=200V, I_B=0$	Min	--	50	μA
	I_{CEX}	$V_{CE}=450V, V_{BE}=1.5V$	Min	500	--	μA
		$V_{CE}=300V, V_{BE}=1.5V$	Min	--	500	μA
Emitter-Cut off Current	I_{EBO}	$V_{EB}=6V, I_C=0$	Min	20	20	μA
DC Current Gain	h_{FE}	$I_C=2mA, V_{CE}=10V$	Max	30	--	
		$I_C=20mA, V_{CE}=10V$		40-160	40-160	
Collector Emitter Saturation Voltage	$V_{CE(Sat)}^1$	$I_C=50mA, I_B=4mA$	Min	0.5	0.5	V
Base Emitter Saturation Voltage	$V_{BE(Sat)}^1$	$I_C=50mA, I_B=4mA$	Min	1.3	1.3	V

SMALL SIGNAL CHARACTERISTICS

Small Signal Current Gain	h_{fe}	$I_C=5mA, V_{CE}=10V, f=1kHz$	Max	25	25	
Output Capacitance	C_{ob}	$V_{CB}=10V, I_E=0, f=1MHz$	Min	10	10	pF
Input Capacitance	C_{ib}	$V_{EB}=5V, I_C=0, f=1MHz$	Min	75	75	pF
Current Gain-Bandwidth Product	f_t	$I_C=10mA, V_{CE}=10V, f=5MHz$	Max	15	15	MHz
Real Part of Input Impedance	$R_{e(hie)}$	$V_{CE}=10V, I_C=5mA, f=1MHz$	Min	300	300	Ω

Note:

1. Pulsed: Pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$

Recommended Reflow Solder Profiles

The recommended reflow solder profiles for Pb and Pb-free devices are shown below.

Figure 1 shows the recommended solder profile for devices that have Pb-free terminal plating, and where a Pb-free solder is used.

Figure 2 shows the recommended solder profile for devices with Pb-free terminal plating used with leaded solder, or for devices with leaded terminal plating used with a leaded solder.

Figure 1





Figure 2




Reflow profiles in tabular form


Profile Feature	Sn-Pb System	Pb-Free System
Average Ramp-Up Rate	~3°C/second	~3°C/second
Preheat		
– Temperature Range	150-170°C	150-200°C
– Time	60-180 seconds	60-180 seconds
Time maintained above:		
– Temperature	200°C	217°C
– Time	30-50 seconds	60-150 seconds
Peak Temperature	235°C	260°C max.
Time within +0 -5°C of actual Peak	10 seconds	40 seconds
Ramp-Down Rate	3°C/second max.	6°C/second max.

Recommended Wave Solder Profiles

The Recommended solder Profile For Devices with Pb-free terminal plating where a Pb-free solder is used



The Recommended solder Profile For Devices with Pb-free terminal plating used with leaded solder, or for devices with leaded terminal plating used with leaded solder




Wave Profiles in Tabular Form

Profile Feature	Sn-Pb System	Pb-Free System
Average Ramp-Up Rate	~200°C/second	~200°C/second
Heating rate during preheat	Typical 1-2, Max 4°C/sec	Typical 1-2, Max 4°C/Sec
Final preheat Temperature	Within 125°C of Solder Temp	Within 125°C of Solder Temp
Peak Temperature	235°C	260°C max.
Time within +0 -5°C of actual Peak	10 seconds	10 seconds
Ramp-Down Rate	5°C/second max.	5°C/second max

PACKAGE DETAILS

TO-39 Metal Can Package



DIM	MIN	MAX
A	8.50	9.39
B	7.74	8.50
C	6.09	6.60
D	0.40	0.53
E	--	0.88
F	2.41	2.66
G	4.82	5.33
H	0.71	0.86
J	0.73	1.02
K	12.700	--
L	42°	48°

All dimensions are in mm

PIN CONFIGURATION

1. Emitter
2. Base
3. Collector



Packing Detail

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
TO-39	500 pcs/polybag	540 gm/500 pcs	3" x 7.5" x 7.5"	20K	17' x 15' x 13.5"	32K	40 kgs



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



Recommended Product Storage Environment for Discrete Semiconductor Devices

This storage environment assumes that the Diodes and transistors are packed properly inside the original packing supplied by CDIL.

- Temperature 5 °C to 30 °C
- Humidity between 40 to 70 %RH
- Air should be clean.
- Avoid harmful gas or dust.
- Avoid outdoor exposure or storage in areas subject to rain or water spraying .
- Avoid storage in areas subject to corrosive gas or dust. Product shall not be stored in areas exposed to direct sunlight.
- Avoid rapid change of temperature.
- Avoid condensation.
- Mechanical stress such as vibration and impact shall be avoided.
- The product shall not be placed directly on the floor.
- The product shall be stored on a plane area. They should not be turned upside down. They should not be placed against the wall.

Shelf Life of CDIL Products

The shelf life of products is the period from product manufacture to shipment to customers. The product can be unconditionally shipped within this period. The period is defined as 2 years.

If products are stored longer than the shelf life of 2 years the products shall be subjected to quality check as per CDIL quality procedure.

The products are further warranted for another one year after the date of shipment subject to the above conditions in CDIL original packing.

Floor Life of CDIL Products and MSL Level

When the products are opened from the original packing, the floor life will start.

For this, the following JEDEC table may be referred:

JEDEC MSL Level		
Level	Time	Condition
1	Unlimited	≤30 °C / 85% RH
2	1 Year	≤30 °C / 60% RH
2a	4 Weeks	≤30 °C / 60% RH
3	168 Hours	≤30 °C / 60% RH
4	72 Hours	≤30 °C / 60% RH
5	48 Hours	≤30 °C / 60% RH
5a	24 Hours	≤30 °C / 60% RH
6	Time on Label(TOL)	≤30 °C / 60% RH



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



Customer Notes

Component Disposal Instructions

1. CDIL Semiconductor Devices are RoHS compliant, customers are requested to please dispose as per prevailing Environmental Legislation of their Country.
2. In Europe, please dispose as per EU Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE).

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered trademark of

Continental Device India Pvt. Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone +91-11-2579 6150, 4141 1112 Fax +91-11-2579 5290, 4141 1119

email@cdil.com www.cdil.com

CIN No. U32109DL1964PTC004291