



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company




BRIDGE RECTIFIERS

REVERSE VOLTAGE - 50 to 1000Volts

FORWARD CURRENT - 1.0 Ampere

DF005S - DF10S

**DFS
SURFACE MOUNT
GLASS PASSIVATED
RoHS compliant**



DF-S

FEATURES:

1. Rating to 1000V PRV
2. Ideal for printed circuit board
3. Low forward voltage drop, high current capability
3. Reliable low cost construction utilizing molded plastic technique results in inexpensive product
4. The plastic material has UL flammability classification 94V-0

APPLICATIONS: Power Supplies, Mobile Charger, LED drivers

ABSOLUTE MAXIMUM RATING (Ta = 25 °C Unless otherwise specified)

PARAMETERS		SYMBOL	DF005S	DF01S	DF02S	DF04S	DF06S	DF08S	DF10S	UNITS
Maximum repetitive peak reverse voltage		V_{RRM}	50	100	200	400	600	800	1000	VOLTS
Maximum RMS voltage		V_{RMS}	35	70	140	280	420	560	700	VOLTS
Maximum DC blocking voltage		V_{DC}	50	100	200	400	600	800	1000	VOLTS
Maximum Average Forward Rectified Current @TA=40°C		$I_{(AV)}$	1.0						Amp	
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load		I_{FSM}	30.0						Amp	
Rating for fusing (t=8.3ms, Ta=25° C)		I^2t	10.40						Amp	
Maximum Forward Voltage at 1.0A DC		V_F	1.10						VOLTS	
Maximum DC reverse current at rated DC blocking voltage	T _A =25°C	I_R	10.0						µA	
	T _A =125°C		500							
Typical junction capacitance (Note 1)		C_J	25.0						pF	
Typical thermal resistance (Note2)		$R_{\theta JA}$	40.0						°C/W	
Operating junction and storage		T _J , T _{STG}	-55 to +155						°C	

Note:

1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC
2. Thermal resistance from junction to ambient mounted on P.C.B with 0.5*0.5"(13*13mm) copper pads.

DF005S - DF10S
Rev01 07022022EEG

Typical Characteristic curves

Fig 1: Forward Current Derating Curve




Fig 4: Maximum Non-Repetitive Surge Current




Fig 2: Typical Junction Capacitance




Fig 5: Typical Forward Characteristics





Fig 3: Typical Reverse Characteristics






Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



Package Details

Package:DFS



Dimensions in inches and (millimeters)

MECHANICAL DATA

1. **Polarity:** As marked on Body
2. **Weight:** 0.02 ounces, 0.38 grams
3. **Mounting position:** Any



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



Recommended Product Storage Environment for Discrete Semiconductor Devices

This storage environment assumes that the Diodes and transistors are packed properly inside the original packing supplied by CDIL.

- Temperature 5 °C to 30 °C
- Humidity between 40 to 70 %RH
- Air should be clean.
- Avoid harmful gas or dust.
- Avoid outdoor exposure or storage in areas subject to rain or water spraying .
- Avoid storage in areas subject to corrosive gas or dust. Product shall not be stored in areas exposed to direct sunlight.
- Avoid rapid change of temperature.
- Avoid condensation.
- Mechanical stress such as vibration and impact shall be avoided.
- The product shall not be placed directly on the floor.
- The product shall be stored on a plane area. They should not be turned upside down. They should not be placed against the wall.

Shelf Life of CDIL Products

The shelf life of products is the period from product manufacture to shipment to customers. The product can be unconditionally shipped within this period. The period is defined as 2 years. If products are stored longer than the shelf life of 2 years the products shall be subjected to quality check as per CDIL quality procedure.

The products are further warranted for another one year after the date of shipment subject to the above conditions in CDIL original packing.

Floor Life of CDIL Products and MSL Level

When the products are opened from the original packing, the floor life will start. For this, the following JEDEC table may be referred:

JEDEC MSL Level		
Level	Time	Condition
1	Unlimited	≤30 °C / 85% RH
2	1 Year	≤30 °C / 60% RH
2a	4 Weeks	≤30 °C / 60% RH
3	168 Hours	≤30 °C / 60% RH
4	72 Hours	≤30 °C / 60% RH
5	48 Hours	≤30 °C / 60% RH
5a	24 Hours	≤30 °C / 60% RH
6	Time on Label(TOL)	≤30 °C / 60% RH



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



Customer Notes

Component Disposal Instructions

1. CDIL Semiconductor Devices are RoHS compliant, customers are requested to please dispose as per prevailing Environmental Legislation of their Country.
2. In Europe, please dispose as per EU Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE).

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered trademark of

Continental Device India Pvt. Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone +91-11-2579 6150, 4141 1112 Fax +91-11-2579 5290, 4141 1119

email@cdil.com www.cdil.com

CIN No. U32109DL1964PTC004291

DF005S - DF10S
Rev01 07022022EEG