



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



**SILICON DIAC
BIDIRECTIONAL TRIGGER DIODE
GLASS PASSIVATED PNP DEVICE**

LLDB3

**SOD - 80C
Mini MELF (LL-34)
RoHS compliant**



SOD-80C
(Mini MELF)

GENERAL DISCRIPTIONS:

Functioning as a Trigger Diode with a Fixed Voltage Reference, LLDB3 can be used in Conjunction with Triacs for Simplified Gate Control Circuits or as a Starting Element in Fluorescent Lamp Ballasts

ABSOLUTE MAXIMUM RATINGS (Ta = 25 °C Unless otherwise specified)

PARAMETER	SYMBOL	VALUE	UNIT
Power Dissipation on Printed Circuit (L=10mm) (Ta=50°C)	P _{tot}	150	mW
Up to Ta = 50oC and Mounted on a Ceramic Substrate of 10mm x 10mm x 0.6mm	P _{tot}	120	mW
Repetitive Peak on-State Current (tp=20ms, f=100Hz)	I _{TRM}	2	A
Storage Temperature Range	T _{stg}	-40 to +125	°C
Junction Temperature Range	T _j	-40 to +110	°C

THERMAL RESISTANCE

Junction to Ambient in free air	R _{th(j-a)}	400	°C/W
Junction-Leads	R _{th(j-l)}	150	°C/W

ELECTRICAL CHARACTERISTICS at (Ta = 25 °C Unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Breakover Voltage ¹	V _{BO}	C = 22nF ² see diagram 1	28	--	36	V
Breakover Voltage Symmetry	[+V _{BO} - -V _{BO}]	C = 22nF ² see diagram 1	--	--	±3	V
Dynamic Breakover Voltage ¹	ΔV± I	D1=[I _{BO} to I _F =10mA] see diagram 1	5	--	--	V
Output Voltage ¹	V _O	see diagram 2	5	--	--	V
Breakover Current ¹	I _{BO}	C = 22nF ²	--	--	50	μA
Rise Time ¹	t _r	see diagram 3	--	1.5		μs
Leakage Current ¹	I _B	V _B = 0.5 V _{BO} max see diagram 1	--	--	10	μA

Note:

1. Electrical characteristic applicable in both forward and reverse directions
- 2.Connected in parallel with the devices.

LLDB3

Rev01 21042021E

CIRCUIT DIAGRAMS




DIAGRAM 1 :Current-voltage characteristics




DIAGRAM 2 :Test circuit for output voltage




DIAGRAM 3 : Test circuit see diagram 2.
 Adjust R for $I_p=0.5A$



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



TYPICAL CHARACTERISTICS CURVES

Fig 1: Power dissipation versus ambient temperature (maximum values)




Fig 2: Relative variation of V_{BO} versus junction temperature (typical values)





Fig 3: Peak pulse current versus pulse duration (maximum value)





Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company




ISO 14001




Package Details

SOD 80C (LL-34) Mini MELF Hermetically Sealed Glass Package




TAPE & REEL

TAPE & REEL



Notes:

1. Maximum of 0.5% of the total number of components per reel may be missing-exclusively at the beginning and at the end of the reel.
2. A maximum of three consecutive components may be missing, provided this gap is followed by six consecutive components.



All Dimensions are in mm

Drawings are not to scale

Packing Detail

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
SOD-80C T&R	2.5K/reel	225 gm/2.5K pcs	9" x 9" x 9"	40K	18" x 12" x 10" 19" x 19" x 20"	80K 320K	7.2 kgs 28.8 kgs

LLDB3

Rev01 21042021E



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



Recommended Product Storage Environment for Discrete Semiconductor Devices

This storage environment assumes that the Diodes and transistors are packed properly inside the original packing supplied by CDIL.

- Temperature 5 °C to 30 °C
- Humidity between 40 to 70 %RH
- Air should be clean.
- Avoid harmful gas or dust.
- Avoid outdoor exposure or storage in areas subject to rain or water spraying .
- Avoid storage in areas subject to corrosive gas or dust. Product shall not be stored in areas exposed to direct sunlight.
- Avoid rapid change of temperature.
- Avoid condensation.
- Mechanical stress such as vibration and impact shall be avoided.
- The product shall not be placed directly on the floor.
- The product shall be stored on a plane area. They should not be turned upside down. They should not be placed against the wall.

Shelf Life of CDIL Products

The shelf life of products is the period from product manufacture to shipment to customers. The product can be unconditionally shipped within this period. The period is defined as 2 years.

If products are stored longer than the shelf life of 2 years the products shall be subjected to quality check as per CDIL quality procedure.

The products are further warranted for another one year after the date of shipment subject to the above conditions in CDIL original packing.

Floor Life of CDIL Products and MSL Level

When the products are opened from the original packing, the floor life will start.

For this, the following JEDEC table may be referred:

JEDEC MSL Level		
Level	Time	Condition
1	Unlimited	≤30 °C / 85% RH
2	1 Year	≤30 °C / 60% RH
2a	4 Weeks	≤30 °C / 60% RH
3	168 Hours	≤30 °C / 60% RH
4	72 Hours	≤30 °C / 60% RH
5	48 Hours	≤30 °C / 60% RH
5a	24 Hours	≤30 °C / 60% RH
6	Time on Label(TOL)	≤30 °C / 60% RH



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



Customer Notes

Component Disposal Instructions

1. CDIL Semiconductor Devices are RoHS compliant, customers are requested to please dispose as per prevailing Environmental Legislation of their Country.
2. In Europe, please dispose as per EU Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE).

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered trademark of

Continental Device India Pvt. Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone +91-11-2579 6150, 4141 1112 Fax +91-11-2579 5290, 4141 1119

email@cdil.com www.cdil.com

CIN No. U32109DL1964PTC004291

LLDB3

Rev01 21042021E