




Continental Device India Pvt. Limited
An IATF 16949, ISO9001 and ISO 14001 Certified Company



SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER

Reverse Voltage - 20 to 100 Volts, Forward Current - 3.0 Amperes

SK32_310



DO-214AB (SMC)

**SMC (DO-214AB)
Surface Mount
Plastic Package
RoHS Compliant**

FEATURES

1. The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
2. For surface mounted applications
3. Metal silicon junction, majority carrier conduction
4. Low power loss, high efficiency
5. Built-in strain relief, ideal for automated placement
6. High forward surge current capability
7. High temperature soldering guaranteed: 250 C/10 seconds at terminals

APPLICATION:

Free wheeling diode, High Speed switching , LED driver, SMPS applications

ABSOLUTE MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Ratings at 25 °C ambient temperature unless otherwise specified.)

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

PARAMETER		SYMBOL	SK32	SK33	SK34	SK35	SK36	SK38	SK310	UNIT
Maximum repetitive peak reverse voltage		V _{RRM}	20	30	40	50	60	80	100	V
Maximum RMS voltage		V _{RMS}	14	21	28	35	42	56	70	V
Maximum DC blocking voltage		V _{DC}	20	30	40	50	60	80	100	V
Maximum average forward rectified		I _(AV)	3.0							A
Peak forward surge current 8.3ms single		I _{FSM}	70							A
Maximum instantaneous forward voltage		V _F	0.55			0.7		0.85		V
Maximum DC reverse current at rated DC blocking voltage	@TA=25°C	I _R	0.5							mA
	@TA=100°C		20		10					
Typical junction capacitance (NOTE 1)		C _J	500			300			pF	
Typical thermal resistance (NOTE 2)		R _{θJA}	55							°C/W
Operating junction temperature range		T _J	-65 to +125			-65 to +150			°C	
Storage temperature range		T _{STG}	-65 to +150							°C

Notes

1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.
2. P.C.B. mounted with 0.2x0.2 "(5.0x5.0mm) copper pad areas

Typical Characteristics Curves

FIG. 1. FORWARD CURRENT DERATING CURVE




FIG. 2. MAXIMUM NON-REPETITIVE PEAK




FIG. 3. TYPICAL INSTANTANEOUS FORWARD




FIG. 4. TYPICAL REVERSE




FIG. 5. TYPICAL JUNCTION CAPACITANCE





FIG. 6. TYPICAL TRANSIENT THERMAL






Continental Device India Pvt. Limited
An IATF 16949, ISO9001 and ISO 14001 Certified Company



Package Details

Package: SMC (DO-214AB) Surface Mount Plastic Package



Dimensions in inches and (millimeters)



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



Recommended Product Storage Environment for Discrete

This storage environment assumes that the Diodes and transistors are packed properly inside the original packing supplied by CDIL.

- Temperature 5 °C to 30 °C
- Humidity between 40 to 70 %RH
- Air should be clean.
- Avoid harmful gas or dust.
- Avoid outdoor exposure or storage in areas subject to rain or water spraying .
- Avoid storage in areas subject to corrosive gas or dust. Product shall not be stored in areas exposed to direct sunlight.
- Avoid rapid change of temperature.
- Avoid condensation.
- Mechanical stress such as vibration and impact shall be avoided.
- The product shall not be placed directly on the floor.
- The product shall be stored on a plane area. They should not be turned upside down. They should not be placed against the wall.

Shelf Life of CDIL Products

The shelf life of products is the period from product manufacture to shipment to customers. The product can be unconditionally shipped within this period. The period is defined as 2 years.

If products are stored longer than the shelf life of 2 years the products shall be subjected to quality check as per CDIL quality procedure.

The products are further warranted for another one year after the date of shipment subject to the above conditions in CDIL original packing.

Floor Life of CDIL Products and MSL Level

When the products are opened from the original packing, the floor life will start.

For this, the following JEDEC table may be referred:

JEDEC MSL Level		
Level	Time	Condition
1	Unlimited	≤30 °C / 85% RH
2	1 Year	≤30 °C / 60% RH
2a	4 Weeks	≤30 °C / 60% RH
3	168 Hours	≤30 °C / 60% RH
4	72 Hours	≤30 °C / 60% RH
5	48 Hours	≤30 °C / 60% RH
5a	24 Hours	≤30 °C / 60% RH
6	Time on Label(TOL)	≤30 °C / 60% RH



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



Customer Notes

Component Disposal Instructions

1. CDIL Semiconductor Devices are RoHS compliant, customers are requested to please dispose as per prevailing Environmental Legislation of their Country.
2. In Europe, please dispose as per EU Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE).

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).



CDIL is a registered trademark of

Continental Device India Pvt. Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone +91-11-2579 6150, 4141 1112 Fax +91-11-2579 5290, 4141 1119

email@cdil.com www.cdil.com

CIN No. U32109DL1964PTC004291